

UNICUBE®

Sixth generation micro elemental analyzer for simultaneous analysis of CHNS as well as O and Cl optionally. Suitable for all organic and many inorganic liquids and solids. UNICUBE easily covers both sub-milligram and three-digit milligram weighing range. **A robust workhorse for a wide variety of applications – whenever highest accuracy, robustness and versatility are essential.** A multitude of optional configurations make UNICUBE fit for any application in modern combustion analysis.



Elemental combustion analyzer

Analyzer	Carbon, hydrogen, nitrogen, sulfur, oxygen*, chlorine*
Concentration analysis of	CHNS, CNS, CHN, CN, N, S, O, Cl
Operating modes	
Design	Compact benchtop with single power supply
Sample introduction	Zero blank patented ball valve system
Furnace design	Double furnace system, 10 years warranty
Gas separation	Direct Temperature Programmed Desorption (direct TPD)
Detector type	High sensitivity thermal conductivity detector, infrared*, electrochemical cell*
Control	Fully digital via external PC (no additional control panels required)
Sample Introduction	
Construction	One block, auto-aligned sample introduction system with integrated carousel
Access	Inert gas free easy access, no purging of sample carousel required
Movement control	Fully electrical
Carousel type	Non-stacked 60*, 80*, 120 or 240* position solid sampler 2ml vial, 50 position random access liquid sampler with rinse and waste vial*
Solid sampling system	Compact integrated patented ball valve
Liquid sampling system*	Radial sample turret with central rotating sample injection arm
Liquid injection port*	Septum-free micro-seal injection port
Syringe injection*	User-exchangeable microsyringe with bubble elimination feature
Injection speed*	User selectable
Dosing resolution*	Min. 24 nl
Gas sampling system*	User controllable manual injection
Furnace	
Type	Slide-out, double vertical furnace system for usage of 28 mm inner diameter quartz or steel**reaction tubes
Furnace	Resistive heater element with 1200°C maximum temperature
Electrical supply	48 Volt safety design for entire instrument including furnaces
Combustion/reduction reactor	Quartz tube long life design with separated combustion and reduction tube
Oxygen reactor*	Quartz tube with carbon black filling
Chlorine reactor*	Quartz tube with tungsten trioxide filling
Ash removal	Quartz easy removal ash finger
Reactor stability	No need for cooling down during routine maintenance
Carrier gas	Helium, argon*, forming gas*, synthetic air*
Connections	Quick swap clamp connections for fast maintenance, no tools required

Gas separation	
Type	Dynamically heated chromatographic separation system using direct temperature programmed desorption technology (direct TPD technology)
No of columns	1
Retention time control	N ₂ , Cl no control, all other gases user defined computer control
Baseline separation	1/12000 N/C and S/C elemental ratio
Column flush system	Full separation of all analytes with patented direct TPD technology, no peak tailing or peak overlap
Recovery rate	100%
Detectors/electronics	
Type	Thermal Conductivity Detector (TCD), 10 years warranty
Design	Thermistor, oxygen proof, indestructable, double channel
Type	SO ₂ specific Infrared*, CO specific infrared*, combined CO+SO ₂ specific infrared*
Design	Built-in, solely software controlled switching to TCD for alternative element detection
Type	Chlorine sensitive electrochemical cell*
Design	Exchangeable 200 ppm and 5000 ppm cell
Detection limit**	< 50 ppm (TCD)
Calibration	Multipoint, multirange, matrix-independent calibration
Analysis time**	~ 7 min for simultaneous CHNS determination, self-optimizing depending on element content and sample weight
Electronics	Fully digital, fully integrated in unit, no external control panels
Security norms	EU machinery directive 2006/42/EG
Software	
Operating system	Windows® 10, other systems upon request
Analyzer software	Proprietary software, own development
Features	Automatic leak finding software Intelligent error indicator with sophisticated self-diagnostics Auto sleep and wake-up Statistical calculations Service cycle indication LIMS integration 21 CFR part 11 compliant*
Balance	Automatic read out of weighing data*

Measuring Range and Specifications

C:	0 – 14 mg absolute or 0 – 100 % (0 – 50* mg in CN mode)	standard deviation**:	<0.1 % absolute (homogeneous substance)
H:	0 – 2 mg absolute or 0 – 100 %	dimensions:	48 x 55 x 57 cm (W x D x H)
N:	0 – 10 mg absolute or 0 – 100 %	weight:	approx. 70 kg
S:	0 – 3 mg absolute or 0 – 100 %	electrical connections:	100/120/220/230/240 V, 50/60 Hz, 1.5 kW
O*:	0 – 6 mg absolute or 0 – 100 %	oxygen consumption:	approx. 0.05 l / analysis
Cl*:	0 – 1.2 mg absolute or 0 – 100 %	required gases:	carrier gas and oxygen only

* requires optional configuration

** depending on sample type, analysis mode and configuration



BRASIL: LABCONTROL LTDA
Fonc: 11-5181-1173
Email: vendas@labcontrol.com.br

Elementar Analysensysteme GmbH

Elementar-Straße 1 · 63505 Langenselbold (Germany)

Phone: +49 (0) 6184 9393-0 | info@elementar.de | www.elementar.de

