


## OCA product series

Optical contact angle measuring and contour analysis systems ranging from basic device to fully automated measuring systems for micro-structured samples



# Optical contact angle measurement and drop contour analysis


The optical analysis of drops that hang from a dosing needle or are placed on a solid surface facilitates the determination of different surface and interfacial parameters. The **contact angle** that a liquid drop establishes on a solid surface characterises the solid's wetting behaviour with said liquid.

Having measured the contact angles of multiple test liquids the **surface energy of the solid** can be determined and the latter can be used to calculate the work of adhesion for different liquids.


The reliable and experimentally robust measurement of the contact angle aids on the development of surface coatings, composite materials, paints and varnishes or cleaning agents. In short: the measurement of contact angle helps in all situations where solids and liquids meet and advantage is to be gained by the control of wetting and adhesion properties.

## Young-Laplace evaluation

When no other factor is in play a drop of liquid tends to form a sphere, due to its surface tension. The typical drop shape materialises because the drop is elongated due to gravity. The Young-Laplace evaluation of pendant drops recognises this fact: The characteristic shape of the drop profile yields the surface tension  $\sigma_L$  of a liquid.



In the case where a pendant drop is surrounded by a second liquid, rather than air, the interfacial tension between the two liquids can be deduced from the drop shape. For optical analysis the outer liquid has to be transparent. Depending on the relative densities, the inner liquid can be dosed either as a pendant drop or upwards, via a bent needle.




## Young equation

An equilibrium of vectorial forces dictates the **contact angle**  $\Theta_c$  at the three phase contact line of a deposited drop. The surface energy of the solid  $\sigma_s$  acts along the solid surface. The solid-liquid interfacial energy  $\sigma_{SL}$  acts in the opposite direction and the surface tension  $\sigma_L$  of the liquid acts tangential to the drop surface. This can be described by a simple scalar equation:

$$\sigma_L \cos \Theta_c = \sigma_s - \sigma_{SL} \quad \text{Young equation}$$

The drop is viewed in profile during the contact angle measurement. The image processing software recognises and records the drop contour, as well as the base line at the solid-liquid interface, and fits a mathematical function to the drop shape.



## Surface energy of solids

To determine the surface energy of a solid one measures the contact angles of test liquids whose surface tensions including their dispersive and polar parts are known. These dispersive and polar parts are used to calculate the interfacial tension  $\sigma_{SL}$  between the solid and a liquid based on a suitable model.


An often applied model is the one of Owens, Wendt, Rabel and Kaelble (**OWRK model**) which considers the geometric mean of the dispersive and polar parts of the liquid's surface tension  $\sigma_L$  and of the solid's surface energy  $\sigma_s$ :

$$\sigma_{SL} = \sigma_s + \sigma_L - 2\sqrt{\sigma_s^d \sigma_L^d} - 2\sqrt{\sigma_s^p \sigma_L^p}$$

Substituting this expression in the Young equation, the polar and the dispersive part of the solid's surface energy can be

determined from the regression line in a suitable plot.

The linear regression requires contact angle measurements with at least two different test liquids. However, as a regression line based on just two points contains no information on the accuracy of the result, contact angle measurements with at least three test liquids are recommended for the determination of the surface energy of solids.




## Lotus effect

A well quoted example of **large contact angles** can be found in nature: when water droplets come into contact with a lotus leaf they roll off without wetting the surface. During 'roll off' the drops take dirt particles with them, resulting in the self-cleaning of the leaf. Mimicking this "Lotus effect" is a popular research and product development topic in many technical fields. Self-cleaning facades, ceramics and other surfaces are regarded as highly desirable. In this context the ability to measure and record contact angles, of course, plays an essential role.




## The OCA models

The optical contact angle measuring and contour analysis systems of the OCA series combine **high resolution optics**, **exact liquid dosing** and **precise sample positioning** into powerful and reliable measuring systems.



The modular approach to all hardware components allows for a multitude of configurations, ranging from **manually operated basic devices** to **fully automated high-performance measuring systems**.

All OCA models are based on a common design philosophy and are built with a **sturdy aluminium metal frame**. Moreover, they all feature a **LED lighting** with manually and software-controlled intensity. Due to an automatic temperature drift compensation a stable and homogeneous illumination of the sample is guaranteed at all times.



### OCA 15EC

The OCA 15EC is the **entry level measuring device** for professional contact angle measurements and drop shape analysis.

The sample table of the OCA 15EC can slide freely in **X- and Y-direction** and is locked into position with its **switchable magnetic base**. In **Z-direction** the sample table is adjustable using **precision mechanics with a hand wheel**.

The fast **6.5-fold zoom lens** with manual focus and adjustable observation angle in combination with the **camera with USB 3 interface** ensures pin-sharp drop images and facilitates the effortless analysis with the SCA software.

With a **single direct dosing system SD-DM** or a **double direct dosing system DD-DM** liquids can be positioned and dosed with one or two **electronic syringe modules ESr-N**, respectively.

**Direct tubeless dosing** of the syringe content and the ability to use cost-saving disposable syringes and needles allow for short preparation times and minimal cleaning efforts.

Even though the OCA 15EC is a high precision measuring device designed for laboratory use, it is highly mobile and can effortlessly be taken apart with two star grip screws and be stored securely in a **transport case**.

### OCA 15LJ

The OCA 15LJ is a special variant of the OCA 15EC that is designed to support the DataPhysics **Liquid Jet systems** like the **Double Liquid Jet system DLJ**.

With the **high-performance camera with USB 3 interface** multiple drops fit into the frame and can be analysed simultaneously due to the higher resolution and **larger field of view**.

The **additional connecting sockets** for accessories/extensions on the side of the illumination housing enable a mounting of up to four syringe modules.

Hence, multiple drops can be simultaneously dosed and analysed for a surface energy determination in **one-click**.






# OCA models

## OCA 25

The OCA 25 is the **all-purpose measuring device** for contact angle measurements and drop shape analysis.

The sample table of the OCA 25 is adjustable along **all three directions in space** via **precision axes with hand wheels**. Hence, a **fast and exact manual positioning** of the sample is always guaranteed, even when using high-performance temperature chambers like the electrical temperature control unit TEC 700.



OCA 25 sample table with precision axes for exact manual positioning

Analysis of even the fastest processes is possible recording up to **3250 frames/s** using the **6.5-fold zoom lens** and the **high-performance camera with USB 3 interface**. Hence, contact angles on adsorbing surfaces like tissues or powders can be measured reliably.

For dosing liquids the manual single and double direct dosing systems SD-DM and DD-DM can be used as well as the



electrical temperature control unit TEC 700 with temperature controller for up to 700 °C



determination of the surface energy with an OCA 25 with a threefold electronic direct dosing system DDE/3 and three electronic syringe modules ESr

**electronic multiple direct dosing systems DDE/x**. The latter are able to electronically position **one to four electronic syringe modules ESr-N**.

Furthermore, a **nanolitre dosing system** can be used to generate extra small liquid drops. Even these are no challenge for the OCA 25 due to its high resolution optics.

## OCA 25 special models

The universal device platform opens the way to special models of the OCA 25, which satisfy even highest customer expectations and cope with the most challenging measuring environments.


The high temperature measuring system **OCA 25-HTV 1800** is capable of measuring contact angles at high temperatures of up to 1800 °C and under vacuum down to 10<sup>-5</sup> mbar or under inert gas atmosphere, respectively.

The **OCA 25-PMC 750** with its high pressure measuring chamber provides the opportunity to measure interfacial tensions and contact angles at pressures of up to 750 bar and under high temperature conditions of up to 200 °C.

Further details on these special models can be found in separate data sheets.



OCA 25-HTV 1800 for contact angle measurements in a high temperature furnace




OCA 25-PMC 750 for high pressure contact angle measurements and drop shape analysis

## OCA 50 & OCA 50EC

The OCA 50 is the **fully automatic** measuring device for the time-saving analysis of the wettability of solid surfaces and the determination of the surface energy of solids.

The sample table of the OCA 50 can be positioned along **all three directions in space** via **electronic high-performance axes**, with both **extraordinary speed** and **highest precision**.



OCA 50 sample table with electronic high-performance axes for automatic positioning

Combined with an **electronic multiple direct dosing system DDE/x** and up to **four electronic syringe modules ESr-N** the determination of surface parameters can be automated completely.

The automation of measurements succeeds easier than ever before thanks to the intuitive automation dialogue of the SCA software and its visual drop



OCA 50EC with a threefold electronic direct dosing system DDE/3 and three electronic syringe modules ESr-N

positioning system. Hence it is possible to determine, for example, the surface energy with four test liquids at different position of even large samples without any manual user intervention. This facilitates a complete and automated sample mapping.


In order to map silicon wafers, electronic turn tables with vacuum fixation are available. They allow to access any position for contact angle measurements, even on 12" wafers.

In any case, the **6.5-fold zoom lens** and the **high-performance camera with USB 3 interface** ensure optimal images of the deposited drops.

For a fast and intuitive device control, even during complex measurements, the **TP 50 control panel with touch screen and precision control wheel** is included with every OCA 50.



OCA 50 on tilting base unit TBU 100



l: electronic turn table with vacuum fixation for automatic wafer mapping  
r: wafer top plate for 6", 8" and 12" wafer



TP 50 control panel with touch screen and precision control wheel




# OCA models

## OCA 200

The OCA 200 is the contact angle measuring and drop contour analysis system for **microscopic and macroscopic structures**.

The **software-controlled, electrically driven optic alignment** enables the OCA 200 to adjust the observation angle and to **focus automatically**.

With the trendsetting **10-fold zoom lens** and the reliable **auto focus system** by DataPhysics, the OCA 200 is equipped to handle any kind of sample size from a macroscopic silicon wafer to the microscopic mesh structure of a coronary stent.



contact angle measurement on a coronary stent using the picolitre dosing system PDDS

In combination with the **high-performance camera with USB 3 interface** even smallest drops of highly volatile liquids can be monitored.

The **electrically driven sample table** makes it possible to position micro-structured samples with **highest precision** and **exceptional speed** for fast automated measuring procedures.

With an **electronic multiple direct dosing system DDE/x** and up to **four electronic syringe modules ESr-N** liq-



contact angle measurements on micro-structured samples using an OCA 200 with nanolitre and picolitre dosing systems

uids can be deposited on a macroscopic sample and its surface parameters can be determined automatically.

For the analysis of micro-structured samples the **nanolitre dosing system** is available which can generate down to 10 nanolitre small droplets. These droplets are small enough to fit, for example, between the screw threads of a dental implant whose surface is to be analysed.

Even smaller structures can be analysed using the **picolitre dosing system PDDS** which can dose down to 30 picolitre small droplets. These allow contact angle measurement, for example, on the individual wires of the mesh structure of a coronary stent or on single fibres.



nanolitre drop between the screw threads of a dental implant



high-performance 10-fold zoom lens with software-controlled optic alignment for adjusting the observation angle and for autofocus



determination of the surface energy using an OCA 200 with DDE/4 and four ESr-N

## Accessories for every task

With **manual and electronic direct dosing systems** up to four liquids can be positioned above the sample table with ease.


The **electronic syringe modules ESr-N** which are used with all dosing systems work with glass or disposable syringes and dose down to typically 1  $\mu$ l small drops. This allows for a comfortable analysis of macroscopic samples.

The appropriate dosing systems for micro-structured samples like precision mechanics, printed circuit boards, medical implants, or single fibres are the



**nanolitre dosing system** and the **picolitre dosing system PDDS**. They reproducibly dose **small droplets of down to 10 nl** and **down to 30 pl**, respectively. Further details are found in a separate data sheet.



electronic syringe module ESr-N



l: single direct dosing system SD-DM  
r: electronic direct dosing system DDE/4



nanolitre dosing system



picolitre dosing system PDDS

For a firm fixation of the samples on the sample table DataPhysics offers multiple options. The sample table **STC 100** features **holding clamps** that reliably and easily fix samples like glass slides. Films or fabric on the other hand can be spanned over the **curved sample table FHM 100** and to which they are fixed with lateral magnetic bars. The **suction plate SP 100** is designed to hold especially flexible samples flat on its suction area, while single fibres are conveniently positioned spanned into the **single fibre holder FHO 40plus**.

The **electronic tilting base unit TBU 100** fully automatically tilts the entire OCA device in a range of **-5° to +95°** including attachments like dosing systems and environmental chambers. This permits dynamic contact angle measurements according to the tilting method and


allows determining the advancing and receding contact angle and contact angle hysteresis as well as the 'roll off' angle for a certain drop volume.



electronic tilting base unit TBU 100  
for dynamic contact angle measurements



holder for single fibres FHO 40plus



l: curved table with magnetic bars FHM 100  
r: suction plate SP 100



## Wide range of accessories

Pursuant to the modular design of the OCA series, DataPhysics provides a wide range of accessories facilitating measurements under various environmental conditions.

With different **environmental chambers** measuring temperatures from **-30 °C to 700 °C** can be reached.


Dedicated to investigating the properties of metals, polymers or hotmelts in their liquid state is the **electrical needle heating device NHD 700**. This special piece of development enables the dosing of **molten solids at temperatures up to 700 °C**. Hence the surface tension of, for example, molten aluminium can be determined.

The **humidity generators of the HGC series** allow for a reliable control of the **relative humidity** in the range of **5 % to 90 %**. The HGC instruments are connected to the environmental chambers from DataPhysics but can also be used with those of other suppliers.

Further details on the HGC series and the thermal solutions are found in separate data sheets.



humidity generator HGC 30




electrical needle heating device NHD 700



liquid temperature control unit TFC 100Pro for temperatures of -10...100 °C



Peltier temperature control unit TPC 160 with temperature controller for -30...160 °C



Topview Video System TVS for contact angle measurements in topview

The **TP 50 control panel with touch screen and precision control wheel** establishes a comfortable and **intuitive control** of **all electrical components** of the OCA series, ranging from the electrically driven sample table over the electronic dosing systems up to any additionally attached modules such as a humidity generator. The precision control wheel allows to make settings exceptionally fast and still with the highest accuracy.

The **Topview Video System TVS** opens up a completely new approach to contact angle measurement. With this system deposited drops are monitored and evaluated in topview which allows to investigate previously inaccessible sample spots, for

example, at the bottom of indents of ready-made components or on assembled printed circuit boards. Moreover, the TVS enables the determination of surface homogeneity and surface isotropy.


The proper piece of equipment to study the interfacial rheology of **oscillating drops** is the **oscillating drop generator ODG 20**. The ODG 20 allows investigations with either constant or varying drop volume.

The **electro wetting platform EWP 100** facilitates the analysis of sessile and pendant drops in a defined electric field.

More information on these and many other accessory options are found on the [DataPhysics website](http://www.dataphysics.com).



TP 50 control panel with touch screen and precision control wheel



oscillating drop generator ODG 20 for oscillation measurements of pendant drops



## Software for an efficient workflow

The SCA software, designed for Microsoft Windows®, is the modular program for all OCA instruments.


The **modern user interface** is highly customisable and offers every user an individual and ideally suited overview during measurements.

A software-integrated **extensive data-base** comprises important physical and chemical parameters of a multitude of liquids and solids.

The SCA software features **recording and storing of movie sequences** which allows for a controlled evaluation of even the fastest processes.

Due to a newly developed **automation dialogue** the automated control of all electronic components becomes effortless. For example, an entire sample can be mapped automatically determining the surface energy with up to four liquids. The position of every drop can either be set according to predefined patterns or individually using the **intuitive visual drop positioning function**.


The SCA software is divided into the following separately available modules:



contact angle measurement with SCA 20

### SCA 20 — contact angle


- measurement and presentation of the static contact angle on plane, convex and concave surfaces according to the sessile drop and the captive drop method
- automatic baseline detection on flat and curved surfaces
- surface roughness correction with optional Surface Profile Analyzer SPA 25
- measurement of dynamic contact angles (advancing and receding angle, contact angle hysteresis) according to the needle-in-drop method and the tilting method



determination of the surface energy with SCA 21

### SCA 21 — surface energy

- determination of the surface energy of solids as well as of its components (e.g. dispersive, polar and hydrogen bond parts, acid and base portions) according to nine different theories
- calculation and representation of wetting envelopes and work of adhesion/contact angle diagrams



surface tension measurement with SCA 22

### SCA 22 — surface/interfacial tension


- determination of the surface and interfacial tension, as well as of their polar and dispersive parts, based on the Young-Laplace evaluation of pendant drops

### SCA 23 — liquid bridge analysis

- determination of the surface and interfacial tension based on the evaluation of the lamella contour
- liquid bridge analysis of 3-phase systems

### SCA 26 — oscillation / relaxation


- determination of the real and the imaginary part of the interfacial dilatational modulus based on the contour of oscillating and relaxing pendant drops



topview measurement with SCA 27

### SCA 27 — contact angle in topview

- determination of the contact angle based on the drop radius analysed in topview measurements and the drop volume



automation dialogue with visual drop positioning

	OCA 15EC	15LJ	OCA 25	OCA 50	50EC	OCA 200
<b>Contact angle [SCA 20]</b>	○		○	○		○
measuring range	0 ... 180°		0 ... 180°	0 ... 180°		0 ... 180°
accuracy	± 0.1°		± 0.1°	± 0.1°		± 0.1°
resolution	± 0.01°		± 0.01°	± 0.01°		± 0.01°
<b>Surface and interfacial tension [SCA 22]</b>	○		○	○		○
measuring range	0.01 ... 2000 mN/m		0.01 ... 2000 mN/m	0.01 ... 2000 mN/m		0.01 ... 2000 mN/m
resolution	± 0.01 mN/m		± 0.01 mN/m	± 0.01 mN/m		± 0.01 mN/m
<b>Surface energy [SCA 21]</b>	○		○	○		○
<b>Liquid bridge analysis [SCA 23]</b>	○		○	○		○
<b>Oscillation / relaxation [SCA 26]</b>	○		○	○		○
<b>Topview contact angle [SCA 27]</b>	—		○	○		○
<b>Sample table</b>	sliding magnetic base		manual precision axes	electronic precision axes		electronic precision axes
traversing range (X-axis [mm] x Y-axis [mm] x Z-axis [mm])	110 x 90 x 42		100 x 104 x 42	100 x 105 x 50		100 x 105 x 50
traversing speed (X- and Y-axis)	—		—	75 nm/s ... 20 mm/s		75 nm/s ... 20 mm/s
traversing speed (Z-axis)	—		—	75 nm/s ... 25 mm/s		75 nm/s ... 25 mm/s
positioning resolution	—		—	± 39 nm		± 39 nm
max. sample weight	3.0 kg (locked Z-axis: 15.0 kg)		3.0 kg (locked Z-axis: 15.0 kg)	10.0 kg		10.0 kg
<b>LED-lighting</b> with manual and software-controlled intensity including automatic temperature drift compensation						
warm-white LED (3000 K)	●		●	●		●
monochromatic red LED (660 nm)	○		○	○		○
monochromatic blue LED (465 nm)	○		○	○		○
<b>Temperature and environmental control</b>						
temperature chambers (-30 °C to 700 °C)	○		○	○		○
electrical needle heating device (RT ... 700 °C)	○		○	○		○
humidity generator of the HGC series	○		○	○		○

● integrated    ○ with optional software/accessory

— not available

	OCA 15EC	15LJ	OCA 25	OCA 50	50EC	OCA 200
<b>Optics</b> 6.5-fold zoom lens with integrated manual focus ( $\pm 6$ mm) 10-fold zoom lens with software-controlled focus ( $\pm 4,5$ mm) and observation angle ( $-9^\circ \dots +2^\circ 2'$ ) <b>field of view</b> (X min x Y min) ... (X max x Y max) (1.11 mm x 0.83 mm) ... (7.14 mm x 5.35 mm) (2.50 mm x 1.33 mm) ... (16.09 mm x 8.55 mm) (1.12 mm x 0.58 mm) ... (11.29 mm x 5.98 mm)	● —	—	● —	● —	—	— ●
	● ○ —	— ● —	— ● —	— ● —	● ○ —	— — ●
<b>Camera system</b> USB 3 camera, 1/3" sensor max. resolution 1448 x 1086 pixel with 156 frames/s, max. frame rate 3246 frames/s with 1448 x 60 pixel USB 3 camera, 2/3" sensor max. resolution 2048 x 1088 pixel with 180 frames/s, max. frame rate 3250 frames/s with 2048 x 60 pixel high-speed camera system	● ○ on request	— ●	— ● on request	— ● on request	● ○	— ● on request
<b>Number of connecting sockets</b> for accessories/extensions	3	7	9	15	9	15
<b>TP 50 control panel</b>	○		○	●	○	●
<b>Dimensions</b> (L [mm] x W [mm] x H [mm])	550 x 160 x 365		660 x 220 x 365		680 x 310 x 370	
<b>Weight</b>	14 kg	15 kg	16 kg	26 kg		28 kg
<b>Power supply</b>	100 ... 240 VAC; 50 ... 60 Hz; 70 W		100 ... 240 VAC; 50 ... 60 Hz; 70 W		100 ... 240 VAC; 50 ... 60 Hz; 70 W	





**For more information please contact us.  
We will find a tailor-made solution to your  
surface chemistry requirements and  
will be pleased to provide a quotation,  
obligation-free, for your instrument system.**

DataPhysics Instruments GmbH • Raiffeisenstraße 34 • 70794 Filderstadt, Germany  
phone +49 (0)711 770556-0 • fax +49 (0)711 770556-99  
[sales@dataphysics-instruments.com](mailto:sales@dataphysics-instruments.com) • [www.dataphysics-instruments.com](http://www.dataphysics-instruments.com)

**Your sales partner:**



Representante Exclusivo no Brasil  
Para maiores informacoes:  
e-mail : [vendas@labcontrol.com.br](mailto:vendas@labcontrol.com.br)  
fone: +55 (11) 5181-1173